

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT QUARTZ+ TOP



Material no.

Specification

154324

Revision date

16.02.2021

Version

1.15

Page

1 of 6

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME : IGL Coatings™ ecocoat quartz+ top  
FUNCTION : Hydro- & oleophobic and easy clean agent surface modifier and gloss enhancer  
COMPANY : Ominent Sdn Bhd  
ADDRESS : No.7, Jalan Majistret U1/26, Hicom-Glenmarie Industrial Park, Seksyen U1, 40150 Shah Alam, Selangor.  
PHONE : +60355690980  
EMAIL ADDRESS : regulations@iglcoatings.com

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008

##### Physical hazards

Flammable liquid Category 3

##### Health hazards

Skin irritation Category 2

Serious eye damage Category 1

Specific target organ toxicity – single exposure Category 3

#### 2.2 Label Elements

Regulation (EC) No. 1272/2008



GHS02



GHS05



GHS07

##### Signal word

Danger

##### Hazard statements

H226 Flammable liquid and vapour  
H317 Causes skin irritation  
H318 Causes serious eye damage  
H336 May cause drowsiness or dizziness

##### Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/fume/gas/vapours.  
P264 Wash exposed skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P370+P378 In case of fire: Use water spray, dry chemical or carbon dioxide to extinguish.  
P403+P235 Store in well-ventilated place. Keep cool.  
P405 Store locked up.

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT QUARTZ+ TOP

Material no.

Specification

Version

154324

1.15

Revision date

Page

16.02.2021

2 of 6



P501

Dispose of contents/container to comply with local, state and federal regulations.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS No.	Chemical Name			Quantity
	EC No.	Index No.	REACH No.	
	Classification according to Regulation (EC) No. 1272/2008 (CLP)			
123-86-4	Butyl acetate			80-100%
	204-658-1	607-025-00-1	01-2119485493-29-0000	
	STOT SE 3: H336; Flam. Liq. 3: H226			
475645-84-2	Organopolysilazane			5-10%
	Not applicable	Not applicable	Not applicable	
	Acute Tox. 4: H302; Flam. Liq. 2: H225; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1: H317			
63148-61-8	Organopolysiloxane			0.1-1%
	814-597-8	Not applicable	Not applicable	
	Not applicable			
7782-42-5	Graphene			0.1-1%
	231-955-3	Not applicable	01-2119486977-12-0000	
	Not applicable			

#### Additional information:

The exact percentage of the ingredients used in this product are considered to be proprietary and are withheld as confidential business information.

### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

##### General Information

Take off contaminated clothing.

##### After Inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

##### After skin contact

Gently wash with plenty of soap and water. In case of skin irritation, seek medical treatment.

##### After contact with eyes

Rinse cautiously with water at least 15 minutes. Remove contact lenses, if presence and easy to do  
In case of troubles or persistent symptoms, consult an ophthalmologist.

##### After ingestion

Rinse mouth thoroughly with water. Do not induce vomiting.

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

#### 5.1 Suitable extinguishing media

Water spray, dry chemical or carbon dioxide.

#### 5.2 Unsuitable extinguishing media

High volume water jet.

#### 5.3 Special hazards arising from the substance or mixture

Hazardous toxic and irritating fumes or smoke may be emitted

Vapours may travel considerable distance to ignition source and flash back

#### 5.4 Advise for firefighters

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear.

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT QUARTZ+ TOP

Material no.

Specification

Version

154324

1.15

Revision date

Page

16.02.2021

3 of 6



### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition

Beware of vapours accumulating to form explosive concentrations. Vapour can accumulate in low areas.

Wear personal protection equipment (refer to section 8).

#### 6.2. Environmental precautions

Discharge into the environment must be avoided.

#### 6.3. Methods and material for containment and cleaning up

Take up mechanically.

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated articles and floor according to the environmental legislation.

#### 6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### 7. HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Do not breath vapour/dust. Avoid contact with eyes. Wash thoroughly with water and soap after handling.

##### Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge

##### Further information on handling

General protection and hygiene measures: refer to section 8.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Further information on handling

##### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

##### Advice on storage compatibility

Do not store together with food and feeding stuffs.

##### Further information on storage conditions

Keep the packing dry and well-sealed to prevent contamination. Recommended storage temperature: 20C

Protect against: UV-radiation/sunlight. heat.

Static electricity may accumulate and cause a fire hazard

#### 7.3. Specific end use(s): refer to section 1.

### 8. EXPOSURE CONTROL/PERSONAL PROTECTION

#### 8.1 Control parameters

##### Ingredients with limit values that require monitoring at the workplace:

Component	Value type (Form of exposure)	Control parameter	Basis
Butyl acetate	TWA	150 ppm 713 mg/m <sup>3</sup>	MY OEL
	TWA	150 ppm	ACGIH
	STEL	200 ppm	ACGIH

#### 8.2 Exposure Control

##### Advice on safe handling

##### 8.2.1 General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Ensure adequate ventilation.

##### 8.2.2 Personal protective equipment:

**Respiratory protection:** Required when aerosols are generated. Recommended filter type: ABEK filter

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT QUARTZ+ TOP



Material no.

Specification

154324

Revision date

16.02.2021

Version

1.15

Page

4 of 6

### Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of protective clothing should take into account all relevant work factors such as: other chemicals which may be handled, physical requirements, etc.

### Material of gloves:

Butyl rubber.

### Penetration time of glove material:

> 10 min

**Eye protection:** Tightly fitting eye goggles.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point	: 126 °C
Vapour Pressure	: 10.66 hPa (at 20°C)
Relative Vapor Density	: 4.0 (Air = 1)
Specific Gravity	: No data available
Melting Point	: Not applicable
Flash Point	: 26°C
pH	: No data available
Evaporation Rate	: Not applicable
Solubility in Water	: Not soluble
Appearance (color)	: Colourless
Appearance (form)	: Liquid
Odour	: Ester-like

## 10. STABILITY AND REACTIVITY

**10.1 Reactivity:** No further relevant information available.

**10.2 Chemical stability:** Stable under normal conditions.

Thermal decomposition / conditions to avoid: No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions:** No dangerous reaction known under conditions of normal use.

**10.4 Conditions to avoid:** Sunlight, heat, open flames, high temperature, sparks, static electrical charge, other ignition sources

**10.5 Incompatible materials:** Strong oxidizing agents.

**10.6 Hazardous decomposition products:** Possible decomposition products in case of hydrolysis: Hydrogen, ammonia, condensed siloxane.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Exposure route	Endpoint	Value	Species
Oral	LD50	2940 mg/kg	Rat
Dermal	LD50	17414 mg/kg	Rabbit

**Skin corrosion/irritation:** May causes mild skin irritation.

**Eye irritation:** May cause mild eye irritation.

**Respiratory or skin sensitization:** No information available.

**Summary of evaluation of the CMR properties:** Shall not be classified as a germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

**Specific target organ toxicity – single exposure:** No information available.

**Specific target organ toxicity – repeated exposure:** No information available.

**Aspiration hazard:** No information available.

## 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

**Specified substance: Butyl acetate**

Endpoint	Value	Species	Exposure time
----------	-------	---------	---------------

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT QUARTZ+ TOP



Material no.

Specification

154324

Revision date

16.02.2021

Version

1.15

Page

5 of 6

LC50	18 mg/L	Fish (Pimephales promelas)	96 hours
EC50	44 mg/L	Water flea (Daphnia magna)	48 hours
ErC50	630 µg/L	Desmodesmus subspicatus (green algae)	72 hours

### Specified substance: Organopolysilazane

Endpoint	Value	Species	Exposure time
LC50	57.1 mg/L	Zebra fish (Danio rerio)	96 hours

### Specified substance: Polysiloxane

Endpoint	Value	Species	Exposure time
LC50	> 100 mg/L	Fish (Pimephales promelas)	96 hours
EC50	> 10000 mg/L	Water flea (Daphnia magna)	48 hours

### 12.2 Process of degradability

No data available.

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available.

### 12.5 Results of PBT and vPvB Assessment

No data available.

### 12.6 Other adverse effects

Discharge into the environment must be avoided.

## 13. DISPOSAL CONSIDERATION

### 13.1 Waste treatment methods

Dispose of contents/container in accordance with local/regional/national/international regulation.

### Sewage disposal-related information

Do not empty into drains.

### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## 14. TRANSPORT INFORMATION

### 14.1 IATA-DGR

UN number : 1263  
UN proper shipping name : Paint related materials  
Transport hazard class(es) : 3  
Packing group : III  
Environmental hazards : -  
Special precautions for user : No data available.

### 14.2 IMDG-Code

UN number : 1263  
UN proper shipping name : Paint related materials  
Transport hazard class(es) : 3  
Packing group : III  
Environmental hazards : --  
Marine pollutant : No

## 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### US Federal Regulations

#### US. Toxic Substances Control Act (TSCA)

# SAFETY DATA SHEET

## IGL COATINGS™ ECOCOAT QUARTZ+ TOP



Material no.

Specification

Version

154324

1.15

Revision date

Page

16.02.2021

6 of 6

All chemical substances in this material are included on the TSCA Inventory of Chemical Substances.

### **Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Hazardous Substance List**

This product contains the following substance subject to the reporting requirements of CERCLA Hazardous Substance List

<b>Component(s)</b>	<b>CAS No.</b>
Butyl acetate	123-86-4

### **Superfund Amendments and Reauthorization Act of 1986 (SARA)**

#### **Emergency Planning and Community Right-To-Know Act (EPCRA) Section 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

#### **Emergency Planning and Community Right-To-Know Act (EPCRA) Section 313 Toxics Release Inventory (TRI) Reporting**

None present or none present in regulated quantities.

### **Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

None present or none present in regulated quantities.

### **US. State Regulation**

#### **US. California Proposition 65**

No ingredient requiring a warning under CA Prop 65.

### **EU Regulation**

#### **EU. Directive 2012/18/EU (SEVESO III) on Major Accident Hazards Involving Dangerous Substances, Annex I:**

Not applicable.

### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

---

## **16. OTHER INFORMATION**

### **Further information**

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material use in combination with any other materials or any process, unless specified in the test.